

ASUS VA27ECPSN

178° Ultra-wide View Docking Monitor



Key Features



Frameless Design

Frameless, edge-to-edge design suitable for multi-display setup



IPS technology panel is optimized for the finest image and color quality with 178° wide-viewing-angle

75 Hz
Refresh Rate

Decimating blurry to gain the upper hand in current video games



USB Type-C Monitor

Full function USB-C connection for DisplayPort video, USB data transmission and supports 65W power delivery



RJ-45

Delivers stable Internet connection and one-cable docking to your laptop with RJ45 and USB-C connection



USB Hub

Satisfies every usage with built-in USB hub and rich connectivity



Eye Care+

ASUS Eye Care+ technology with flicker free and low blue light ensures a comfortable viewing experience



4-way Ergonomic Stand

With an ergonomically-designed stand with tilt, swivel, pivot, and height adjustments



Wall Mountable

Compatible with VESA wall-mount standard

Specification

Display	Panel Size : Wide Screen 27-inch (68.6 cm), 16:9 Display Viewing Area (HxV) : 597.89 x 336.31 mm Panel Type : IPS True Resolution : Full HD 1920 x 1080 Pixel Pitch : 0.311 mm Brightness(Max) : 300 cd/m ² Contrast Ratio : 1,000:1 ASUS Smart Contrast Ratio (ASCR) : 100,000,000:1 Viewing Angle (CR \geq 10) : 178°(H)/178°(V) Color Saturation : 72% NTSC Response Time : 5ms (Gray to Gray) Display Colors : 16.7M Flicker Free : Yes	
Video Feature	Blue Light Filter : Yes Trace Free Technology : Yes SPLENDID Technology : 8 Modes (Standard / Scenery / Night View / Game / Theater / sRGB / Reading / Darkroom) Color Temperature Selection : 4 Modes (Cool / Normal / Warm / User) Skin-Tone Selection : 3 mode HDCP support : Yes, 1.4 Vivid Pixel Technology : Yes GamePlus : Yes (Crosshair / Timer / FPS Counter / Display Alignment) QuickFit : 3 modes (Alignment Grid / Document / Photo) Adaptive-Sync : 60~75Hz Eye Care+ Technology : Yes	
Audio Feature	2W x 2 Stereo RMS	
I/O Ports	Signal Input : USB-C x 1 DisplayPort 1.2 x 1 HDMI (v1.4) x 1 RJ45 x 1 USB-C Power Delivery : 65W	USB Hub: USB3.2 Gen 1 Type-A x 3 Earphone Jack : Yes, 3.5mm Mini-Jack
Signal Frequency	Digital Signal Frequency : 30~84 KHz (H) / 48~75 Hz (V)	
Power Consumption	Power on (Typical) : < 20W Power Saving Mode : < 0.5W Power Off Mode : < 0.3W Voltage : 100-240V, 50 / 60Hz	
Mechanical Design	Chassis Colors : Black Tilt : +35° ~ -5° Swivel : +180° ~ -180°	Pivot : 90° (Clockwise & Anticlockwise) Height Adjustment : 0 ~ 150 mm VESA Wall Mounting : 100 x 100 mm
Security	Kensington lock	
Dimensions	Phys. Dimension with Stand (WxHxD) : 612.42 x (373.33~523.33) x 226.30 mm Phys. Dimension without Stand (WxHxD) : 612.42 x 367.03 x 47.20 mm Box Dimension (WxHxD) : 680 x 475 x 170 mm	
Weight	Net Weight (Esti.) : 6.48 Kg Net Weight without Stand (For VESA Wall Mount) (Esti.) : 3.64 Kg Gross Weight (Esti.) : 8.52 Kg	
Accessories	Power Cord, USB-C cable (optional), DisplayPort cable (optional), HDMI cable (optional), Warranty card, Quick Start Guide	
Compliance Standard	UL/cUL, ICES-3, CB, CE, CEC, ErP, WEEE, ISO 9241-307, UkrSEPRO, CU, CCC, CEL, BSMI, RCM, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, e-Standby, Energy Star, TCO Edge, RoHS, WHQL Windows 10/11, EPEAT Silver, TÜV Flicker Free, TÜV Low Blue Light	

*Power consumption is measured with screen brightness of 200 nits without audio / USB / or other peripheral connections drawing power.

**All specifications are subject to change without notice