

ASUS BE24EQSB

Business Monitor with Highly Ergonomic Design



Height Adjustment
(0 to 130mm)



Swivel(+180° to -180°)



With mini PC
mounting kit (option)



Tilt(-5° to 35°)




Pivot(+90° to -90°)

Key Features



IPS technology is optimized for the finest image quality with 178° wide-viewing-angle



Frameless Design

Frameless panel design for an ideal multi display setup



DisplayPort

Extensive connectivity with DisplayPort, HDMI, D-sub, Audio in, Earphone jack



4-way Ergonomic
Stand

Ergonomically-designed stand with tilt, swivel, pivot, and height adjustments



Wall Mountable

Compatible with VESA Wall Mount Standard (100 x 100 mm).



USB Hub

Embedded four USB 3.2 Gen 1 Type-A ports for connecting mouse, keyboard, or other USB devices



Stereo Speaker

Built-in 2W stereo speakers for audio experience



Flicker-free

ASUS Flicker-Free Technology clears out the distracting flicker, and brings viewing comfort.



Ultra-low
Blue Light

Four levels of Blue Light Filter help users effectively reduce harmful blue light from the screen by tasks.

Specification

Display	Panel Size(diagonal)	23.8"(60.47cm) Wide Screen (16:9)
	Display Viewing Area(HxV)	527.04 x 296.46 mm
	Panel Type	IPS
	Display Surface	non-glare
	Color Saturation	72% NTSC
	True Resolution	1920 x 1080
	Pixel Pitch	0.2745 mm
	Brightness (Max.)	300cd/m ²
	Contrast Ratio (Max.)	1000:1
	ASUS Smart Contrast Ratio(ASCR)	100,000,000:1
	Viewing Angle (CR _≥ 10)	178°(H)/178°(V)
	Display Colors	16.7 million
	Response Time	5ms (GTG)
Video Features	Splendid Video Intelligence Tech.	Yes
	Skin-Tone Selection	3 modes
	Color Temperature Selection	4 modes (Cool/Normal/Warm/User)
	HDCP	Yes
	QuickFit	Yes
Blue Light Filter	Yes	
Audio Features	Stereo Speaker	2W x 2 stereo, RMS
Input/ Output		HDMI, DisplayPort, D-Sub, Audio-in, Earphone jack, USB 3.2 Gen 1 ports (1up, 4 down)
Signal Frequency	Digital/ Analog Signal Frequency	Digital Signal Frequency : 30~83 KHz (H) / 47~76 Hz (V) Analog Signal Frequency : 30~83 KHz (H) / 49~76 Hz (V)
Power	Power Consumption	<15 W* ¹
	Power Saving Mode	<0.5W
	Power Off Mode	0W(hard switch)
	Voltage	100–240V, 50 / 60 Hz
Mechanical Design	Chassis Colors	Black
	Tilt(angle)	Yes (+35° ~ -5°)
	Swivel(angle)	Yes (+180° ~ -180°)
	Pivot(angle/direction)	Yes (+90° ~ -90°)
	Height Adjustment	Yes (0~130mm)
VESA Wall Mounting	100x100mm	
Security	Kensington lock	Yes
Dimension	Phys. Dimension (WxHxD)	540x(332~462)x211mm (with stand), 540x330x47mm(without stand)
	Box Dimension (WxHxD)	649 x474x192mm
Weight	Net: 7.8kg (with stand) , 5.0kg (without stand), Gross: 10.5 kg	
Accessories	Power cord(1.8m), VGA cable (1.8m, optional) , DP Cable(1.8m, optional), HDMI cable(1.8m, optional), Audio cable(1.8m, optional), USB cable(1.8m), Warranty card, Quick Start Guide, MiniPC Kit(optional)	
Compliance Standards	Energy Star®, UL/cUL, CB, CE, FCC, CU, RCM, VCCI, PSE, ErP, TCO, RoHS, WEEE, Windows 7/8/10 WHQL, ISO 9241-307, TUV-Flicker Free, TUV-GS, TUV-LBL, TUV-Ergo, KC, KCC, standby, ICES-3, UkrSEPRO, CCC, CEL, BSMI, PC Recycle, J-MOSS	

*1.Measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection

*2.All specifications are subject to change without notice.

Outline Dimension

