

# ProArt Display PA148CTV

The Shortcut to Creativity



## Key Features



Low Blue Light  
& Flicker Free



IPS technology is optimized for the finest image quality with 178° wide-viewing-angle



International color standard 100% sRGB / 100% Rec. 709 color space for digital images and video production



Factory pre-calibrated with ASUS advanced gray-scale tracking technology to guarantee the  $\Delta E$  color difference value is less than 2



10-point Touch

Capacitive 10-point multi-touch capability and Windows 10 compatible



USB Type-C Monitor

USB-C and micro-HDMI ports provide rich connectivity



Control Panel

Virtual Control Panel Integrate Software provides shortcut and customized hotkey to enhance productivity



ASUS Dial

Intuitive ASUS Dial control integrate software and support Microsoft Dial provides shortcut and customized hotkey to enhance productivity



Eye Care

TÜV Rheinland-certified Flicker-free and Low Blue Light technologies to ensure a comfortable viewing experience




Ergo Kick Stand

Ergo Kick Stand design provides intuitive tilt angle adjustment with landscape and portrait view

ASUS

# ProArt Display PA148CTV

## Spec Sheet

<p><b>Display</b></p>	<p>Panel Size : 14-inch (35.56 cm) Wide Screen (16:9)          Display Viewing Area (HxV) : 309.37 x 174.02 mm          Panel Backlight / Type : IPS          True Resolution : 1920 x 1080          Pixel Pitch : 0.160 mm          Display Colors : 16.7M          Color Saturation : 100% sRGB / 100% Rec. 709          Brightness : 300 cd/m<sup>2</sup> (typical)          Contrast Ratio: 700:1 (typical)          ASUS Smart Contrast Ratio (ASCR) : 100,000,000:1          Viewing Angle (CR≥10) : 178° (H)/178° (V)          Response Time : 5ms (GTG)          Flicker-free : Yes          Touch Screen : Yes, Capacitive 10-point multi-touch</p>
<p><b>Video Feature</b></p>	<p>Trace Free Technology : Yes          ProArt Preset : 9 modes (Standard / sRGB / Rec. 709 / DCI-P3 / Scenery / Reading / Darkroom / User mode1 / User mode2)          Color Accuracy : <math>\Delta E &lt; 2</math>          ProArt Palette : Yes          Gamma Adjustment : Yes (Support Gamma 2.6, 2.4, 2.2, 2.0, and 1.8)          Color Adjustment : 6-axis (R, G, B, C, M, Y)          Color Temperature Selection : 5 modes          QuickFit : Yes (Square / Alignment Grid / Ruler)          HDCP support : Yes, 1.4          Adaptive-Sync support: Yes (40~60Hz)</p>
<p><b>Audio Feature</b></p>	<p>1W x 2 stereo, RMS</p>
<p><b>IO ports</b></p>	<p><b>Signal Input :</b>          USB-C x 2          micro HDMI (v1.4) x 1</p>  <p>micro HDMI          USB-C          USB-C</p>
<p><b>Power Consumption</b></p>	<p>Power On (Typical): &lt;4.67W          Power Saving Mode : &lt;0.5W          100-240V, 50/60Hz</p>
<p><b>Mechanical Design</b></p>	<p>Tilt : 15° ~ 75°          Pivot : 90° (Clockwise)          Tripod Hole: Yes</p>
<p><b>Dimensions</b></p>	<p>Phys. Dimension with Stand (WxHxD) : 326.1 x 204.4 x 12.0 mm          Box Dimension (WxHxD) : 413 x 342 x 90 mm</p>
<p><b>Weight</b></p>	<p>Net Weight (Esti.) : 0.74 kg, Gross Weight (Esti.) : 2.5 kg</p>
<p><b>Accessories</b></p>	<p>Power Adaptor, USB-C cable (optional), HDMI to micro HDMI cable (optional), USB-C to USB-A Cable (optional), USB-C to USB-A adaptor (optional), Calibration Report, Quick Start Guide, Warranty Card, Welcome Card, ProArt Sleeve</p>
<p><b>Compliance Standard</b></p>	<p>Energy Star®, CB, CE Doc., FCC, CCC, BSMI, CU, RVCCI, ErP, CEC, HF, RoHS, WEEE, PC Recycle, WHQL, KCC, KC, e-Standby, TÜV Flicker Free, TÜV Low Blue Light, Calman Verified</p>

\* Power Consumption is measuring a screen brightness of 200 nits without audio / USB / Card reader connection

\*\*All specifications are subject to change without notice