## ASUS VA24DQSB

## 178° Ultra-wide View with Eye Care Monitor





## **Key Features**



Frameless Design

Frameless, edge-to-edge design suitable for multidisplay setup



IPS technology panel is optimized for the finest image and color quality with 178° wide-viewing-angle



Decimating blurry to gain the upper hand in current video games



Exclusive GamePlus function provides the accurate and perfect gaming experience



Extensive connectivity with HDMI and DisplayPort ports for incredible home-theater entertainment



**USB Hub** 

Satisfies every usage with built-in USB hub and rich connectivity



TÜV Rheinland-certified ASUS Flicker-Free and Low Blue Light technologies



Stand

With an ergonomicallydesigned stand with tilt, swivel, pivot, and height adjustments



Compatible with VESA wallmount standard



## **Specification**

Panel Size: Wide Screen 23.8-inch (60.45 cm) LED backlight, 16:9 Display Viewing Area (HxV): 527.04 x 296.46 mm Panel Type: WLED / IPS True Resolution: Full HD 1920 x 1080 Pixel Pitch: 0.2745 mm Brightness(Max): 250 cd/m<sup>2</sup> **Display** Contrast Ratio: 1,000:1 ASUS Smart Contrast Ratio (ASCR): 100,000,000:1 Viewing Angle (CR≥10): 178°(H)/178°(V) Color Saturation: 72% NTSC Response Time: 5ms (Gray to Gray) Display Colors: 16.7M Flicker Free: Yes Blue Light Filter: Yes Trace Free Technology: Yes SPLENDID Video Intelligence Technology: Yes SPLENDID Video Preset Modes: 8 Modes (Standard / Scenery / Night View / Game / Theater / sRGB / Reading / Darkroom) Color Temperature Selection: 4 Modes (Cool / Normal / Warm / User) **Video Feature** Skin-Tone Selection: 3 mode HDCP support: Yes Vivid Pixel Technology: Yes GamePlus: Yes (Crosshair / Timer / FPS Counter) QuickFit: 3 modes (Alignment Grid / Document / Photo) Adaptive-Sync: 48 - 75Hz **Audio Feature** 2W x 2 Stereo RMS PC audio-in: Signal Input: DisplayPort1.2 x 1 Yes, 3.5mm Mini-Jack HDMI(v1.4) x 1 D-sub x 1 **Earphone Jack:** Yes, 3.5mm Mini-Jack USB Hub: 2x USB 2.0 Type-A I/O Ports Audio-in DisplayPort HDMI D-sub (VGA) **()** Earphone out USB Hub (1U, 2D) Analog Signal Frequency: 30~83 KHz (H) / 50~75 Hz (V) **Signal Frequency** Digital Signal Frequency: 30~85 KHz (H) / 48~75 Hz (V) Power on (Typical): < 16.7W Power Saving Mode: < 0.3W **Power Consumption** Power Off Mode: < 0.3W Voltage: 100-240V, 50 / 60Hz Chassis Colors: Black Pivot: 90° (Clockwise& Anticlockwise) Tilt: +35° ~ -5° Height Adjustment: 0 ~ 130 mm **Mechanical Design** Swivel:  $+180^{\circ} \sim -180^{\circ}$ VESA Wall Mounting: 100 x 100 mm Kensington lock Security Phys. Dimension with Stand (WxHxD): 540 x (320~450) x 211 mm Phys. Dimension without Stand (WxHxD): 540 x 325 x 54 mm **Dimensions** Box Dimension (WxHxD): 634 x 450 x 228 mm Net Weight (Esti.): 5.31 kg Net Weight without Stand (For VESA Wall Mount) (Esti.): 3.21 kg Weight Gross Weight (Esti.): 6.8 kg Power Cord, DisplayPort cable (optional), HDMI cable (optional), VGA cable (optional), Audio cable (optional), **Accessories** USB cable (optional), Warranty card, Quick Start Guide Energy Star®, FCC, cTUVus, ICES-3, CB, CE, ErP, WEEE, TUV-GS, TUV-Ergo, ISO 9241-307, UkrSEPRO, CU, CCC,

CEL, BSMI, RCM, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, e-Standby, TCO, WHQL Windows 7/10,

TÜV Flicker Free, TÜV Low Blue Light

**Compliance Standard** 



 $<sup>\</sup>ensuremath{^*}$  measuring a screen brightness of 200 nits without audio / USB / Card reader connection

<sup>\*\*</sup>All specifications are subject to change without notice