

# ASUS BE24ECSNK

## Video Conferencing Monitor



PC mounted

## Key Features



178° wide-viewing-angle IPS panel (Full HD) exudes consistent color at almost any viewing angle.



Webcam with Mic Array

Built in adjustable 2MP 1080p webcam, mic array plus stereo speakers deliver better online communication.



DisplayPort

Extensive connectivity of USB-C, HDMI, DP in, DP out for daisy chain, USB hub and Earphone jack



AI Mic Noise Cancellation

Integrates the AI Noise-Canceling Mic to eliminate almost all unwanted noise to retain only your voice clearly heard.



Face Auto Exposure

Face Auto Exposure technology detects your face automatically to make your face look brighter.



USB Type-C

Support signal transmission of DisplayPort, data transmission and up to 80W power delivery via just one USB-C cable.



RJ-45

With RJ45 and USB-C, the monitor delivers stable Internet connection and one-cable docking to your laptop.



4-way Ergonomic Stand

Ergonomically-designed stand with tilt, swivel (+180° ~ -180°), pivot, and height adjustments



Wall Mountable

Space saving from compatible VESA mount standard (100 x 100 mm) and bundled ASUS miniPC kit (optional)



Flicker Free  
Low Blue Light  
Content  
www.asus.com  
ID: 0217008144



(By country)

# Specification

Display	Panel Size(diagonal)	23.8"(60.45 cm) Wide Screen (16:9)
	Display Viewing Area(HxV)	527.04 x 296.46mm
	Panel Type	IPS
	Display Surface	non-glare
	Color Saturation	72% NTSC
	True Resolution	1920x1080
	Pixel Pitch	0.2745mm
	Brightness (Max.)	300cd/m <sup>2</sup>
	Contrast Ratio (Max.)	1000:1
	ASUS Smart Contrast Ratio(ASCR)	100,000,000:1
	Viewing Angle (CR <sub>≥</sub> 10)	178°(H)/178°(V)
	Display Colors	16.7 million
	Response Time	5ms (GTG)
Video Features	Splendid™ Video Intelligence Tech.	Yes
	Skin-Tone Selection	3 modes
	Color Temperature Selection	4 modes (Cool/Normal/Warm/User)
	HDCP support	Yes (ver. 1.4)
	QuickFit	Yes
	Blue Light Filter	Yes
Webcam (built-in)	Yes (2M 1080p; Swivel +180° ~ -135°, Tilt +10° ~ -10°)	
Audio Features	Built-in Microphone(Array type) Stereo Speaker 2W x 2, RMS	
Input/ Output	USB-C DP Alt mode with PD 80W, HDMI, DP, DP output(for daisy-chain), USB3.2 Gen1 x4 ports (downstream), Earphone jack , RJ45	
Signal Frequency	Digital Signal Frequency	30~85 KHz (H) / 48~75 Hz (V)
Power	Power Consumption	<17.7 W* <sup>1</sup>
	Power Saving Mode	<0.5W
	Power Off Mode	0W(hard switch)
	Voltage	100~240V, 50 / 60 Hz
Mechanical Design	Color	Black
	Tilt(angle)	Yes (+35° ~ -5°)
	Swivel(angle)	Yes (+180° ~ -180°)
	Pivot(angle/direction)	Yes (+90° ~ -90°)
	Height Adjustment	Yes (0~150mm)
VESA Wall Mounting	100x100mm	
Security	Kensington lock	Yes
Dimension	Phys. Dimension (WxHxD)	539.7 x (401.02~538.89) x 211.4 mm(with stand+webcam), 539.7 x 389.89 x 61.0 mm(without stand)
	Box Dimension (WxHxD)	722 x 481 x 182 mm
Weight	Net Weight with Stand : 6.5 Kg Net Weight without Stand : 4.3 Kg Gross Weight : 8.9 Kg	
Accessories	Power cord(1.8m), HDMI cable(1.8m), USB-C cable(1.5m), DisplayPort Cable(optional), USB C to A Cable(optional), Warranty card, Quick Start Guide, mini PC kit(optional)	
Compliance Standards	Energy Star®, TCO 9.0, EPEAT Silver(by country), UL, FCC, ICES-003, CB, CE, ErP, WEEE, EU Energy label, ISO 9241-307, UkrSEPRO., CU, Ru RoHs, CCC, China RoHs, CEL, BSMI, RCM, MEPS, VCCI, PSE, PC-Recycle, J-MOSS, KC, KCC, e-Standby, RoHs, CEC, WHQL Windows 7/10/11, TUV Flicker free, TUV Low Blue Light, NFPA 99, Zoom Certified	

\*1.Measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection

\*.All specifications are subject to change without notice.

