

# ProArt Display PA328QV



## Key Features



**QHD**  
**2560x1440**

Supporting QHD 2560x1440 resolution for crystal clear image quality



IPS technology is optimized for the finest image quality with 178° wide-viewing-angle



International color standard 100% sRGB / 100% Rec. 709 color space for digital images and video production



Factory pre-calibrated with ASUS advanced gray-scale tracking technology to guarantee the  $\Delta E$  color difference value is less than 2



ProArt Palette

ProArt Palette to adjust color parameters delivers all consistency and quickly adjust to see different color performance



Extensive connectivity with DisplayPort, HDMI, Audio in, Earphone jack



Frameless Design

Frameless panel design for an ideal multi display setup



USB Hub

Embedded USB ports for connecting mouse, keyboard, or other USB devices




4-way Ergonomic Stand

Ergonomically-designed stand with tilt, swivel, pivot, and height adjustments

# ProArt Display PA328QV

## Spec Sheet

<b>Display</b>	<p>Panel Size : 31.5-inch (80.098cm) Wide Screen (16:9)          Display Viewing Area(HxV) : 698.112 x 392.688 mm          Display Surface : Non-Glare          Panel Type : IPS          Viewing Angle (CR≥10, H/V) : 178° / 178°          Pixel Pitch : 0.272 mm          Resolution : 2560x1440          Color Space (sRGB) : 100%          Color Space (Rec. 709) : 100%          Brightness (HDR, Peak) : 400 cd/m<sup>2</sup> / (Typ.) : 350cd/m<sup>2</sup>          Contrast Ratio (Typ.) : 1000:1          Display Colors : 1073.7M (10 bit)          Response Time : 5ms (GTG)          Refresh Rate (Max) : 75Hz          HDR (High Dynamic Range) Support : HDR-10          Flicker-free : Yes</p>
<b>Video Feature</b>	<p>Trace Free Technology : Yes          ProArt Preset :          Standard / sRGB / Rec. 709 / DCI-P3 / HDR / Scenery / Reading / Rapid Rendering / User Mode 1 / User Mode 2          Color Temp. Selection : Yes (5 modes)          Color Adjustment : 6-axis adjustment (R,G,B,C,M,Y)          Gamma adjustment : Yes (Support Gamma 1.8/2.0/2.2/2.4/2.6)          Color Accuracy : ΔE &lt; 2          ProArt Palette : Yes          QuickFit Plus : Yes          PIP / PBP Technology : Yes          HDCP : Yes, 2.2          VRR Technology : Adaptive-Sync          Low Blue Light : Yes</p>
<b>Audio Feature</b>	<p>Speaker : Yes (2Wx2)</p>
<b>IO ports</b>	<p>DisplayPort 1.2 x 1          HDMI(v2.0) x 2</p> <p>USB Hub : Yes (USB 3.2 Gen1 Type-A x 4)          Earphone Jack : Yes</p> 
<b>Signal Frequency</b>	<p>Digital Signal Frequency :          HDMI : 27~112 KHz (H), 24~75 Hz (V)          DisplayPort : 112~112 KHz (H), 48~75 Hz (V)</p>
<b>Power Consumption</b>	<p>Power On (Typical) : &lt; 23.96W          Power Saving Mode : &lt; 0.5W ; Power Off Mode : 0W (Hard Switch)          100-240V, 50/60Hz</p>
<b>Mechanical Design</b>	<p>Tilt : Yes (+23° ~ -5°)          Swivel : Yes (+30° ~ -30°)          Pivot : Yes (+90° ~ -90°)</p> <p>Height Adjustment : 0~130mm          VESA Wall Mounting : 100x100mm          Kensington Lock : Yes</p>
<b>Dimensions (Est.)</b>	<p>Phys. Dimension with Stand (W x H x D) : 714.8 x (465.6 ~ 595.6) x 245.0 mm          Phys. Dimension without Stand (W x H x D) : 714.8 x 422.2 x 67.33 mm          Box Dimension (W x H x D) : 841 x 525 x 317 mm</p>
<b>Weight (Est.)</b>	<p>Net Weight with Stand : 11.5 kg          Net Weight without Stand : 7 kg          Gross Weight : 14.6 kg</p>
<b>Accessories</b>	<p>Power cord, HDMI cable (optional), DisplayPort cable (optional), USB cable (optional), Calibration Report, Quick Start Guide, Warranty Card, Welcome Card</p>
<b>Compliance Standard</b>	<p>Energy Star®, FCC, UL/cUL, ICES-3, CB, CE, ErP, WEEE, TUV-GS, TUV-Ergo, ISO 9241-307, UkrSEPRO, CU, CCC, CEL, BSMI, RCM, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, e-Standby, PSB, TCO, RoHS, CEC, WHQL Windows 7/10/11, TÜV Flicker Free, TÜV Low Blue Light, EPEAT Silver</p>

\* Power Consumption is measuring a screen brightness of 200 nits without audio / USB / Card reader connection

\*\*All specifications are subject to change without notice

