


ProArt Display PA328CGV



Key Features



QHD
2560x1440

Supporting QHD 2560 x 1440 resolution for crystal clear image quality

HDR
High Dynamic Range

Up to 600 nits brightness with HDR for lifelike contrast & color that brings out details like never before

IPS
Ultra-wide Viewing Angles

IPS technology is optimized for the finest image quality with 178° wide-viewing-angle

165 Hz
Rapid Refresh Rate

Decimating blurry and delivers smooth and crisp video rendering

95% DCI-P3

Up to 95% DCI-P3 international color standard of digital cinema industry

Color Accuracy
 $\Delta E < 2$

Factory pre-calibrated with ASUS advanced gray-scale tracking technology to guarantee the ΔE color difference value is less than 2


USB Type-C Monitor

USB-C connection for DisplayPort, USB data transmission and supports 90W power delivery


Desk Mount Kit

A convenient mounting clamp is included to help free up desk space


4-way Ergonomic Stand

Ergonomically-designed stand with tilt, swivel, pivot, and height adjustments

ASUS

ProArtDisplay PA328CGV

Spec Sheet

Display	<p>Panel Size : 32-inch (81.28cm) Wide Screen (16:9) Display Viewing Area(HxV) : 708.48 x 398.52 mm Panel Backlight / Type : IPS True Resolution : 2560 x 1440 Pixel Pitch : 0.277 mm Display Colors : 1073.7M (10 bit) Color Saturation : 95% DCI-P3, 100% sRGB/Rec.709 Brightness : 450 cd/m² (typical), 600 cd/m² (peak) Contrast Ratio : 1000:1 (typical) ASUS Smart Contrast Ratio (ASCR) : 100,000,000:1 Viewing Angle (CR≥10) : 178°(H)/178°(V) Response Time : 5ms (GTG) Flicker-free : Yes HDR support : Yes, HDR-10 Refresh Rate (Max) : 165Hz</p>
Video Feature	<p>Trace Free Technology : Yes ProArt Preset : 10 modes (Standard / sRGB / Rec.709 / DCI-P3 / Rapid Rendering / HDR / Scenery / Reading / User mode1 / User mode2) Color Accuracy : $\Delta E < 2$ ProArt Palette : Yes Gamma Adjustment : Yes (Support Gamma 2.6, 2.4, 2.2, 2.0, and 1.8) Color Adjustment : 6-axis (R, G, B, C, M, Y) Color Temperature Selection : 5 modes Picture-in-Picture : Yes Picture-by-Picture : Yes (support up to 2 windows) QuickFit+ : Yes (Center Marker / Safety Area / Ruler / Customization) HDCP support : Yes, 2.2 FreeSync Premium Pro support: Yes (48 ~ 165Hz)</p>
Audio Feature	<p>2W x 2 stereo, RMS</p>
IO ports	<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>Signal Input : DisplayPort 1.4 x 1 HDMI (v2.0) x 2 USB-C x 1 USB-C Power Delivery : 90W</p> </div> <div style="width: 45%;"> <p>Earphone Jack : Yes (3.5mm Mini-jack)</p> <p>USB Hub: 4x USB 3.2 Gen 1 Type-A</p> </div> </div> <div style="text-align: center; margin-top: 10px;"> <p style="font-size: small; text-align: center;"> HDMI(v2.0) HDMI(v2.0) DisplayPort1.4 Earphone Jack USB-C USB-A </p> </div>
Signal Frequency	<p>Digital Signal Frequency : HDMI: 30~222 KHz (H) / 48~144 Hz (V) USB-C, DisplayPort: 30~250 KHz (H) / 48~165 Hz (V)</p>
Power Consumption	<p>Power On (Typical): <26.4W Power Saving Mode : < 0.5W ; Power Off Mode : 0W (Hard Switch) 100-240V, 50/60Hz</p>
Mechanical Design	<p>Tilt : +23° ~ -5° Swivel : +30° ~ -30° Pivot : 90° (Clockwise& Anticlockwise)</p> <p style="text-align: right;">Height Adjustment : 0 ~ 130 mm VESA Wall Mounting : 100 x 100 mm Desk C-Clamp Support</p>
Dimensions	<p>Phys. Dimension with Stand (WxHxD) : 727.08 x (471.48~601.48) x 245 mm Phys. Dimension without Stand (WxHxD) : 727.08 x 428.13 x 67.72 mm Box Dimension (WxHxD) : 840 x 516 x 280 mm</p>
Weight	<p>Net Weight (Esti.) : 11.7 Kg, Without Stand (Esti.) : 7.15 Kg, Gross Weight (Esti.) : 16.8 Kg</p>
Accessories (vary by regions)	<p>Power cord, USB-C cable (optional), HDMI cable (optional), DisplayPort cable (optional), Desk C-Clamp, Calibration Report, Quick Start Guide, Warranty Card, Welcome Card</p>
Compliance Standard	<p>Energy Star®, FCC, UL/cUL, cTUVus, ICES-3, CB, CE, ErP, WEEE, ISO 9241-307, UkrSEPRO, CU, CCC, CEL, CECP, BSMI, Taiwan Energy Label, RCM, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, SDcC, e-Standby, PSB, BIS, VN MEPS, TCO, RoHS, NOM, CEC, WHQL Windows 7/10/11, TÜV Flicker Free, TÜV Low Blue Light, Calman Verified, VESA DisplayHDR 600</p>

* Power Consumption is measuring a screen brightness of 200 nits without audio / USB / Card reader connection

**All specifications are subject to change without notice