

ROG Series																
Model		ROG RYUJIN II 360		ROG RYUJIN II 240		ROG RYUJIN 360		ROG RYUJIN 240		ROG RYUO 240		ROG RYUO 120				
Water Block	Water Block Dimension		78.15 x 87.5 x 81 mm				100 x 100x 70mm				80 x 80 x 45mm					
	Block Material		Copper				Copper				Copper					
	Embedded FAN		V				V				-					
	- Fan Speed		4,800 RPM +/- 10%				4,800 RPM +/- 10%				-					
	- Air Pressure		3.23 mmH2O				3.23 mmH ₂ O				-					
	- Air Flow		19.41 CFM				19.41 CFM				-					
	- Fan Noise		31 dB(A)				31 dB(A)				-					
	CPU Socket Support		Intel: LGA 1700, 115x, 1200, 1366,2011,2011-3,2066				Intel: LGA 115x, 1200, 1366,2011,2011-3,2066				Intel: LGA 115x, 1200, 1366,2011,2011-3,2066					
			AMD: AM4, TR4/sTRX4*				AMD: AM4, TR4/sTRX4*				AMD: AM4, TR4/sTRX4*					
*The mounting bracket is bundled with TR4/sTRX4 CPU Package.				*The mounting bracket is bundled with TR4/sTRX4 CPU Package.				*The mounting bracket is bundled with TR4/sTRX4 CPU Package.								
Radiator	Radiator Dimension		394 x 121 x 27mm		272 x 121 x 27mm		394 x 121 x 27mm		272 x 121 x 27mm		272 x 121 x 27mm		150 x 122 x 27mm			
	Radiator Material		Aluminum				Aluminum				Aluminum					
	Tube		Sleeved Rubber tube (380mm)				Sleeved Rubber tube (380mm)				Sleeved Rubber tube (380mm)					
Fan	Fan		3 x Noctua NF-F12 IndustrialPPC 2000 PWM		2 x Noctua NF-F12 IndustrialPPC 2000 PWM		3 x Noctua NF-F12 IndustrialPPC 2000 PWM		2 x Noctua NF-F12 IndustrialPPC 2000 PWM		2 x ROG radiator fan		1 x ROG radiator fan			
	Fan size		3 Fan Slots (120mm)		2 Fan Slots (120mm)		3 Fan Slots (120mm)		2 Fan Slots (120mm)		2 Fan Slots (120mm)		1 Fan Slots (120mm)			
	Fan Dimension		120 x 120 x 25mm				120 x 120 x 25mm				120 x 120 x 25mm					
	Fan Speed		450~2,000 RPM +/- 10%				450~2,000 RPM +/- 10%				800~ 2500 RPM +/- 10%					
	Fan Static Pressure		3.94 mmH ₂ O				3.94 mmH ₂ O				5.0 mmH ₂ O					
	Fan Air Flow		71.6 CFM / 121.8 m ³ h				71.6 CFM / 121.8 m ³ h				80.95 CFM / 137.5 m ³ h					
	Fan Noise		29.7 dB(A)				29.7 dB(A)				37.6 dB(A)					
	Control Mode		PWM/DC				PWM/DC				PWM/DC					
Special Features	AURA Fan		-				-				-					
	OLED Display		3.5" Color LCD				1.77" Full Color OLED				1.77" Full Color OLED					
	AURA Sync Support		V				V				V					
Package Contents			1 x Liquid cooler (pre-applied thermal compound)		1 x Liquid cooler (pre-applied thermal compound)		1 x Liquid Cooler (pre-applied thermal compound)		1 x Liquid Cooler (pre-applied thermal compound)		1 x Liquid Cooler (pre-applied thermal compound)		1 x Liquid Cooler (pre-applied thermal compound)			
			3 x 120mm fan		2 x 120mm fan		3 x 120 mm Radiator Fan		2 x 120 mm Radiator Fan		2 x 120 mm Radiator Fan		1 x 120 mm Radiator Fan			
			1 x 1 to 3 Y-cable for fan connection		1 x 1 to 2 Y-cable for fan connection		Accessory Pack of Screws and brackets		Accessory Pack of Screws and brackets		Accessory Pack of Screws and brackets		Accessory Pack of Screws and brackets			
			1 x ARGB input cable		1 x ARGB input cable		Quick Start Guide.		Quick Start Guide.		Quick Start Guide.		Quick Start Guide.			
			1 x Accessory pack of screws and brackets		1 x Accessory pack of screws and brackets						1 x USB cable for software control		1 x USB cable for software control			
			1 x Quick start guide		1 x Quick start guide											
			1 x ROG sticker		1 x ROG sticker											
			1 x ROG fan controller 3M mounting tape		1 x ROG fan controller 3M mounting tape											
1 x AIO fan controller		1 x AIO fan controller														
Warranty			6 Years				3 Years				3 Years					

ROG Strix LC Series (ARGB)							
Model		ROG Strix LC II 360 ARGB	ROG Strix LC II 360 ARGB White Edition	ROG Strix LC II 240 ARGB	ROG Strix LC II 240 ARGB White Edition	ROG Strix LC II 120 ARGB	ROG Strix LC II 280 ARGB
Water Block	Water Block Dimension	80 x 80 x 45mm					
	Block Material	Copper					
	CPU Socket Support	Intel: LGA 1700, 115x, 1200, 1366,2011,2011-3,2066					
		AMD: AM4, TR4/sTRX4*					
*The mounting bracket is bundled with TR4/sTRX4 CPU Package.							
Radiator	Radiator Dimension	394 x 121 x 27mm		272 x 121 x 27mm		150 x 122 x 27mm	143 x 315 x 30mm
	Radiator Material	Aluminum					
	Tube	Sleeved Rubber tube (380mm)					
Fan	Fan	3 x ROG radiator fan		2 x ROG radiator fan		1 x ROG radiator fan	2x ROG STRIX FAN MODEL 14 ARGB
	Fan size	3 Fan Slots (120mm)		2 Fan Slots (120mm)		1 Fan Slot (120mm)	2 Fan Slots (140mm)
	Fan Dimension	120 x 120 x 25mm					
	Fan Speed	800~ 2500 RPM +/- 10%					
	Fan Static Pressure	5.0 mmH ₂ O					
	Fan Air Flow	80.95 CFM / 137.5 m3h					
	Fan Noise	37.6 dB(A)					
	Control Mode	PWM/DC					
	AURA Fan	ARGB Fan					
Special Features	OLED Display	-					
	AURA Sync Support	V					
Package Contents		1 x Liquid Cooler (pre-applied thermal compound)	1 x Liquid Cooler (pre-applied thermal compound)	1 x Liquid Cooler (pre-applied thermal compound)	1 x Liquid Cooler (pre-applied thermal compound)	1 x Liquid Cooler (pre-applied thermal compound)	1 x Liquid Cooler (pre-applied thermal compound)
		3 x 120mm fan	3 x 120mm fan	2 x 120mm fan	2 x 120mm fan	1 x 120mm fan	2 x 140mm fan
		1 x USB Cable for Software control	1 x USB Cable for Software control	1 x USB Cable for Software control	1 x USB Cable for Software control	1 x USB Cable for Software control	1 x USB Cable for Software control
		1 x 1 to 3 Y-cable for Fan connection	1 x 1 to 3 Y-cable for Fan connection	1 x 1 to 2 Y-cable for Fan connection	1 x 1 to 2 Y-cable for Fan connection	1 x 1 to 2 ARGB spliter cable	1 x 1 to 2 Y-cable for Fan connection
		1 x 1 to 4 ARGB spliter cable	1 x 1 to 4 ARGB spliter cable	1 x 1 to 4 ARGB spliter cable	1 x 1 to 4 ARGB spliter cable	1 x Accessory Pack of Scews and brackets	1 x 1 to 4 ARGB spliter cable
		1 x Accessory Pack of Scews and brackets	1 x Accessory Pack of Scews and brackets	1 x Accessory Pack of Scews and brackets	1 x Accessory Pack of Scews and brackets	1 x Quick Start Guide	1 x Accessory Pack of Scews and brackets
		1 x Quick Start Guide	1 x Quick Start Guide	1 x Quick Start Guide	1 x Quick Start Guide	1 x ROG Sticker	1 x Quick Start Guide
		1 x ROG Sticker	1 x ROG Sticker	1 x ROG Sticker	1 x ROG Sticker	1 x ROG Sticker	1 x ROG Sticker
Warranty		6 Years					

ROG Strix LC Series (RGB)							
Model		ROG Strix LC 360 RGB		ROG Strix LC 240 RGB	ROG Strix LC 120 RGB	ROG Strix LC 360 RGB White Edition	ROG Strix LC 240 RGB White Edition
Water Block	Water Block Dimension	80 x 80 x 45mm			80 x 80 x 45mm		
	Block Material	Copper			Copper		
	CPU Socket Support	Intel: LGA 115x, 1200, 1366,2011,2011-3,2066			Intel: LGA 115x, 1200, 1366,2011,2011-3,2066		
		AMD: AM4, TR4/sTRX4*			AMD: AM4, TR4/sTRX4*		
	*The mounting bracket is bundled with TR4/sTRX4 CPU Package.			*The mounting bracket is bundled with TR4/sTRX4 CPU Package.			
Radiator	Radiator Dimension	394 x 121 x 27mm	272 x 121 x 27mm	150 x 122 x 27mm	394 x 121 x 27mm	272 x 121 x 27mm	
	Radiator Material	Aluminum			Aluminum		
	Tube	Sleeved Rubber tube (380mm)			Sleeved Rubber tube (380mm)		
Fan	Fan	3x ROG RGB radiator fan	2x ROG RGB radiator fan	1 x ROG radiator fan	3x ROG RGB radiator fan	2x ROG RGB radiator fan	
	Fan size	3 Fan Slots (120mm)	2 Fan Slots (120mm)	1 Fan Slot (120mm)	3 Fan Slots (120mm)	2 Fan Slots (120mm)	
	Fan Dimension	120 x 120 x 25mm			120 x 120 x 25mm		
	Fan Speed	800~ 2500 RPM +/- 10%			800~ 2500 RPM +/- 10%		
	Fan Static Pressure	5.0 mmH ₂ O			5.0 mmH ₂ O		
	Fan Air Flow	80.95 CFM / 137.5 m ³ h			80.95 CFM / 137.5 m ³ h		
	Fan Noise	37.6 dB(A)			37.6 dB(A)		
	Control Mode	PWM/DC			PWM/DC		
AURA Fan	ARGB Fan			ARGB Fan			
Special Features	OLED Display	-			-		
	AURA Sync Support	V			V		
Package Contents		1 x Liquid Cooler (pre-applied thermal compound)	1 x Liquid Cooler (pre-applied thermal compound)	1 x Liquid Cooler (pre-applied thermal compound)	1 x Liquid Cooler (pre-applied thermal compound)	1 x Liquid Cooler (pre-applied thermal compound)	
		3 x 120mm fan	2 x 120mm fan	1x 120mm fan	3 x 120mm fan	2 x 120mm fan	
		1 x USB Cable for Software control	1 x USB Cable for Software control	1 x USB Cable for Software control	1 x USB Cable for Software control	1 x USB Cable for Software control	
		1 x 1 to 3 Y-cable for Fan connection	1 x 1 to 2 Y-cable for Fan connection	1 x 1 to 2 ARGB splitter cable	1 x 1 to 3 Y-cable for Fan connection	1 x 1 to 2 Y-cable for Fan connection	
		1 x 1 to 4 ARGB splitter cable	1 x 1 to 4 ARGB splitter cable	1 x Accessory Pack of Screws and brackets	1 x 1 to 4 ARGB splitter cable	1 x 1 to 4 ARGB splitter cable	
		1 x Accessory Pack of Screws and brackets	1 x Accessory Pack of Screws and brackets	1 x Quick Start Guide	1 x Accessory Pack of Screws and brackets	1 x Accessory Pack of Screws and brackets	
		1 x Quick Start Guide	1 x Quick Start Guide		1 x Quick Start Guide	1 x Quick Start Guide	
Warranty		5 Years			5 Years		

ROG Strix LC Series													
Model		ROG Strix LC II 360		ROG Strix LC II 240		ROG Strix LC 360		ROG Strix LC 240		ROG Strix LC 120			
Water Block	Water Block Dimension	80 x 80 x 45mm				80 x 80 x 45mm							
	Block Material	Copper				Copper							
	CPU Socket Support	Intel: LGA 1700, 115x, 1200, 1366,2011,2011-3,2066				Intel: LGA 115x, 1200, 1366,2011,2011-3,2066							
		AMD: AM4, TR4/sTRX4*				AMD: AM4, TR4/sTRX4*							
		*The mounting bracket is bundled with TR4/sTRX4 CPU Package.				*The mounting bracket is bundled with TR4/sTRX4 CPU Package.							
Radiator	Radiator Dimension	394 x 121 x 27mm		272 x 121 x 27mm		394 x 121 x 27mm		272 x 121 x 27mm		150 x 122 x 27mm			
	Radiator Material	Aluminum				Aluminum							
	Tube	Sleeved Rubber tube (380mm)				Sleeved Rubber tube (380mm)							
Fan	Fan	3 x ROG radiator fan		2 x ROG radiator fan		3 x ROG radiator fan		2 x ROG radiator fan		1 x ROG radiator fan			
	Fan size	3 Fan Slots (120mm)		2 Fan Slots (120mm)		3 Fan Slots (120mm)		2 Fan Slots (120mm)		1 Fan Slot (120mm)			
	Fan Dimension	120 x 120 x 25mm				120 x 120 x 25mm							
	Fan Speed	800~ 2500 RPM +/- 10%				800~ 2500 RPM +/- 10%							
	Fan Static Pressure	5.0 mmH2O				5.0 mmH2O							
	Fan Air Flow	80.95 CFM / 137.5 m3h				80.95 CFM / 137.5 m3h							
	Fan Noise	37.6 dB(A)				37.6 dB(A)							
	Control Mode	PWM/DC				PWM/DC							
	AURA Fan	-				-							
Special Features	OLED Display	-				-							
	AURA Sync Support	V				V							
Package Contents		1 x Liquid Cooler (pre-applied thermal compound)		1 x Liquid Cooler (pre-applied thermal compound)		1 x Liquid Cooler (pre-applied thermal compound)		1 x Liquid Cooler (pre-applied thermal compound)		1 x Liquid Cooler (pre-applied thermal compound)			
		3 x 120mm fan		2 x 120mm fan		3 x 120 mm Radiator Fan		2 x 120 mm Radiator Fan		1 x 120 mm Radiator Fan			
		1 x USB Cable for Software control		1 x USB Cable for Software control				1 x USB Cable for Software control		1 x USB Cable for Software control		1 x USB Cable for Software control	
		1 x 1 to 3 Y-cable for Fan connection		1 x 1 to 2 Y-cable for Fan connection				1 x 1 to 3 Y-cable for Fan connection		1 x 1 to 2 Y-cable for Fan connection		1 x Accessory Pack of Screws and brackets	
		1 x Accessory Pack of Screws and brackets		1 x Accessory Pack of Screws and brackets				1 x Accessory Pack of Screws and brackets		1 x Accessory Pack of Screws and brackets		1 x Quick Start Guide	
		1 x Quick Start Guide		1 x Quick Start Guide				1 x Quick Start Guide		1 x Quick Start Guide			
		1 x ROG Sticker		1 x ROG Sticker									
Warranty		6 Years				5 Years							

TUF Gaming LC Series									
Model		TUF Gaming LC 240 ARGB		TUF Gaming LC 120 ARGB		TUF Gaming LC 240 RGB		TUF Gaming LC 120 RGB	
Water Block	Water Block Dimension	80 x 80 x 45 mm				80 x 80 x 45 mm			
	Block Material	Copper				Copper			
	CPU Socket Support	Intel: LGA 1700, 115x, 1200, 1366,2011,2011-3,2066				Intel: LGA 115x, 1200, 1366,2011,2011-3,2066			
		AMD: AM4				AMD: AM4			
Radiator	Radiator Dimension	272 x 121 x 27mm		150 x 122 x 27mm		272 x 121 x 27mm		150 x 122 x 27mm	
	Radiator Material	Aluminum				Aluminum			
	Tube	Sleeved Rubber tube (380mm)				Sleeved Rubber tube (380mm)			
Fan	Fan	2x TUF Gaming ARGB radiator fan		1x TUF Gaming ARGB radiator fan		2x TUF Gaming RGB radiator fan		1x TUF Gaming RGB radiator fan	
	Fan size	2 Fan Slots (120mm)		1 Fan Slot (120mm)		2 Fan Slots (120mm)		1 Fan Slot (120mm)	
	Fan Dimension	120 x 120 x 25mm				120 x 120 x 25mm			
	Fan Speed	800 - 2000 RPM +/- 10%				800 - 2000 RPM +/- 10%			
	Fan Static Pressure	3.0 mmH ₂ O				3.0 mmH ₂ O			
	Fan Air Flow	67 CFM / 113.8 m3h				67 CFM / 113.8 m3h			
	Fan Noise	29 dB(A)				29 dB(A)			
	Control Mode	PWM/DC				PWM/DC			
	AURA Fan	ARGB Fan				RGB Fan			
Special Features	OLED Display	-				-			
	AURA Sync Support	V				V			
Package Contents		1 x Liquid Cooler (pre-applied thermal compound)		1 x Liquid Cooler (pre-applied thermal compound)		1 x Liquid Cooler (pre-applied thermal compound)		1 x Liquid Cooler (pre-applied thermal compound)	
		2 x 120 mm Radiator Fan		1 x 120 mm Radiator Fan		2 x 120 mm Radiator Fan		1 x 120 mm Radiator Fan	
		1 x Accessory Pack of Screws and brackets		1 x Accessory Pack of Screws and brackets		1 x Accessory Pack of Screws and brackets		1 x Accessory Pack of Screws and brackets	
		1x Quick Start Guide.		1 x Quick Start Guide.		1 x Quick Start Guide.		1 x Quick Start Guide.	
		1 x 1 to 3 Y-Cable for ARGB Control		1 x 1 to 2 Y-Cable for ARGB Control		1 x 1 to 3 Y-Cable for RGB Control		1 x 1 to 2 Y-Cable for RGB Control	
		1 x 1 to 2 Y-Cable for Fan control		1 x TUF Gaming Sticker		1 x 1 to 2 Y-cable for fan connection			
		1 x TUF Gaming Sticker							
Warranty		6 Years				5 Years			