

ASUSPRO C422AQH

Business Monitor



Key Features



Low Blue Light
& Flicker Free



IPS technology panel is optimized for the finest image and color quality with 178° wide-viewing-angle



DisplayPort

Extensive connectivity with DisplayPort, HDMI, DVI-D, D-sub, Audio in, Earphone jack



USB Hub

Embedded two USB3.0 ports for connecting mouse, keyboard, or other USB devices



Flicker-free

ASUS Flicker-Free Technology clears out the distracting flicker, and brings viewing comfort.



Ultra-low Blue Light

Four setting levels of Blue Light Filter help users effectively reduce harmful blue light from the screen by tasks.



Backlight

Adopt mercury-free LED backlight that results power savings and eco-friendliness



Wall Mountable

Compatible with VESA Wall Mount Standard (100 x 100 mm).



Stereo Speaker

Built-in 2W stereo speakers for audio experience



Complied with ENERGY STAR® for environmental protection & money saving

Specification

Display	Panel Size(diagonal)	21.5" (54.6cm)Wide Screen (16:9)
	Display Viewing Area(HxV)	476.064 (H) x 267.786(V)mm
	Panel Type/ Backlight	IPS/ WLED backlight
	Display Surface	non-glare
	Color Saturation	72% NTSC
	True Resolution	1920 X 1080
	Pixel Pitch	0.248 mm
	Brightness (Max.)	250cd/m ²
	Contrast Ratio (Max.)	1000:1
	ASUS Smart Contrast Ratio(ASCR)	100,000,000:1
	Viewing Angle (CR \geq 10)	178°(H)/178°(V)
	Display Colors	16.7 million
Response Time	5ms (GTG)	
Video Features	Splendid™ Video Intelligence Tech.	Yes
	Skin-Tone Selection	3 modes
	Color Temperature Selection	4 modes (Cool/Normal/Warm/User)
	HDCP	Yes
	QuickFit	Yes
	Blue Light Filter	Yes
	VividPixel	Yes
Audio Features	Stereo Speaker	2W x 2 stereo, RMS
Input/ Output	HDMI, DisplayPort, DVI-D, D-Sub, Audio-in, Earphone jack, USB3.0 ports (1up, 2 down)	
Signal Frequency	Analog Signal Frequency	30~83 KHz(H)/ 49~76 Hz(V)
	Digital Signal Frequency	30~83 KHz(H)/ 49~76 Hz(V)
Power	Power Consumption	13.05W*
	Power Saving Mode	<0.5W
	Power Off Mode	0W(hard switch)
	Voltage	100–240V, 50 / 60 Hz
Mechanical Design	Chassis Colors	Black
	Tilt(angle)	+20° ~ -5°
	VESA Wall Mounting	100x100mm
Security	Kensington lock	Yes
Dimension	Phys. Dimension (WxHxD)	514 x 383 x 195 mm (with stand)
		514 x 312 x 50 mm(without stand)
	Box Dimension (WxHxD)	576 x120x 442 mm
Weight	3.8 Kg(Net with stand); 1.53 kg(Net without stand); 5.3Kg (Gross)	
Accessories	Power cord (1.5m), VGA cable (1.5m), DP Cable (1.8m), HDMI cable (optional), Audio cable (1.5m), USB cable (1.5m), Warranty card, Quick Start Guide	
Compliance Standards	Energy Star®, UL/cUL, CB, CE, FCC, CU, RCM, MEPS, VCCI, PSE, ErP, TCO 7.0, RoHS, WEEE, EPEAT(optional), Windows 7/8/10 WHQL, ISO 9241-307, Flicker Free, LBL, EMC DoC, UkrSEPRO, TUV-GS, TUV-Ergo	

*measuring a screen brightness of 200 nits without audio / USB / Card reader connection

**All specifications are subject to change without notice.