

ASUS VA27EHE

178° Ultra-wide View with Eye Care Monitor



Low Blue Light & Flicker Free

Key Features



Frameless Design

Frameless, edge-to-edge design suitable for mu



IPS technology panel is optimized for the finest image and color quality with 178° wide-viewing-angle

75 Hz
Refresh Rate

Decimating blurry to gain the upper hand in current video games



Exclusive GamePlus function provides the accurate and perfect gaming experience



Exclusive QuickFit technology enhance editing scenario



Extensive connectivity with HDMI ports for incredible home-theater entertainment



Flicker-free

To eliminate the disturbing flickers on screen to reduce eye fatigue



Ultra-low Blue Light

You could choose from 4 levels of Ultra-low Blue Light modes for your best viewing and users scenario




Wall Mountable

Compatible with VESA wall-mount standard



Specification

Display	<p>Panel Size : Wide Screen 27-inch (68.5 cm) LED backlight, 16:9 Display Viewing Area (HxV) : 597.89 x 336.31 mm Panel Type : WLED / IPS True Resolution : Full HD 1920 x 1080 Pixel Pitch : 0.3114 mm Brightness(Max) : 250 cd/m² Contrast Ratio : 1,000:1 ASUS Smart Contrast Ratio (ASCR) : 100,000,000:1 Viewing Angle (CR_{≥10}) : 178°(H)/178°(V) Color Saturation : 72% NTSC Response Time : 5ms (Gray to Gray) Display Colors : 16.7M Flicker Free : Yes</p>
Video Feature	<p>Blue Light Filter : Yes Trace Free Technology : Yes SPLENDID Video Intelligence Technology : Yes SPLENDID Video Preset Modes : 8 Modes (Standard / Scenery / Night View / Game / Theater / sRGB / Reading / Darkroom) Color Temperature Selection : 4 Modes (Cool / Normal / Warm / User) Skin-Tone Selection : 3 mode HDCP support: Yes Vivid Pixel Technology : Yes GamePlus : Yes (Crosshair / Timer / FPS Counter / Display Alignment) QuickFit : 3 modes (Alignment Grid / Document / Photo) Adaptive-Sync : 48 – 75Hz</p>
I/O Ports	<p>Signal Input : HDMI x 1 D-sub x 1</p> <div style="text-align: center;"> <p>HDMI D-sub (VGA)</p>  </div>
Signal Frequency	<p>Analog Signal Frequency : 24~84 KHz(H)/ 48~75 Hz(V) Digital Signal Frequency : 24~84 KHz(H)/ 48~75 Hz(V)</p>
Power Consumption	<p>Power on (Typical) : <30W * Power Saving Mode : < 0.5W Power Off Mode : <0.5W Voltage : 100-240V, 50 / 60Hz</p>
Mechanical Design	<p>Chassis Colors : Black Tilt : -5° ~ 23° VESA Wall Mount (100x100 mm)</p>
Security	<p>Kensington lock</p>
Dimensions	<p>Phys. Dimension with Stand (WxHxD) : 612.24 x 453.73 x 239.94 mm Phys. Dimension without Stand (WxHxD) : 612.24 x 366.67 x 48.90 mm Box Dimension (WxHxD) : 684 x 471 x 146 mm</p>
Weight	<p>Net Weight (Esti.) : 4.64 kg Net Weight without Stand (For VESA Wall Mount) (Esti.) : 4.03 kg Gross Weight (Esti.) : 6.14 kg</p>
Accessories	<p>Power Cord, HDMI cable (optional), VGA cable (optional), Warranty card, Quick Start Guide</p>
Compliance Standard	<p>Energy Star®, UL, CB, CE, FCC, ICES-3, CCC, BSMI, CU, RCM, MEPS, CEC, TCO8.0, CEL, HF, RoHS, WEEE, Windows 7/8.1/10 WHQL, ISO9241, TÜV-GS, TÜV-EG, KCC, KC, e-Standby, TÜV-Flicker free, TÜV-Low Blue Light, UkrSEPRO</p>

*measuring a screen brightness of 200 nits without audio / USB / Card reader connection

*All specifications are subject to change without notice.